

DuPont™ Tyvek®

Protection You Can Trust. Every Year, Millions of DuPont™ Tyvek®
Garments Protect People in Various Applications



WARNINGS:

It is the user's responsibility to determine the nature and level of hazard and the proper personal protection equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher penetration rates than the fabric. Please contact DuPont for specific data. These garments are intended for limited use and should be disposed of after single use. If fabric becomes torn, abraded or punctured, end user should discontinue use of garment to avoid potential exposure.

- 1). Tyvek®, ProShield® and Tychem® garments are not flame-resistant and should not be used around heat, flame, sparks or in potentially flammable or explosive environments.
- 2). Garments made of Tyvek®, ProShield® and Tychem® should have slip-resistant or anti-slip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping may occur.

Disclaimer

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience becomes available. DuPont does not guarantee results and, subject to any non-excludable rights you have under the laws in your country (including rights under the Australian Consumer Law), DuPont assumes no obligation or liability in connection with this information.

It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk.

Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, except for those guarantees, warranties or conditions that are guaranteed under the laws in your country (such as the Australian Consumer Law, which gives you certain non-excludable rights for acceptable quality and fitness for disclosed purpose), all other warranties, conditions or guarantees (whether express or implied), including but not limited to warranties of merchantability or fitness for a particular purpose are excluded and subject to those laws in your country, DuPont assumes no liability in connection with any use for this information.

This information is not intended as a licence to operate under or a recommendation to infringe any patent or technical information of DuPont or other persons covering any material or its use.

DuPont reserves its right to make minor changes to the products featured in this catalogue.

DuPont Protection Technologies

Australia

Toll-free: 1800-789-308

Enquiries: e-mail to: personal.protection@aus.dupont.com

New Zealand

Toll-free: 0800-65-8080



Tyvek.

DPT-IPP194 06/2012 AUST

Copyright © 2012 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™ and Tyvek® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

www.personalprotection.dupont.com



DuPont™ Tyvek® Garments

Because Protection, Durability and Comfort are the Ultimate Combination

Touch any garment from the comprehensive DuPont™ Tyvek® product range and you will notice the difference. It is a unique and versatile material that is tough, yet extremely light and soft. Tyvek® was invented and is manufactured exclusively by DuPont. Tyvek® is air and water vapour permeable, yet repels water-based liquids and aerosols. It acts as an excellent barrier against particles and fibres. It is low-linting and also antistatically treated. It also helps to prevent human contamination of products and processes in clean-room environments.



Applications

- Agrochemical handling
- Aluminium and lead smelters
- Asbestos
- Automotive industry
- Cement
- Chemical industry
- Cleanroom applications
- Contaminated land clean-up
- Decontamination of contaminated land and work sites
- Disease management
- Disposal of hazardous materials

- Electronics
- Emergency response services
- Fibreglass
- Food processing
- Industrial cleaning and maintenance
- Medical applications
- Mining and mineral processing
- Nuclear industry
- Pharmaceuticals
- Spray painting

Design

- Ergonomic 3 piece hood allowing easy movement of head without disturbing the view of the wearer
- Tyvek® zipper with zip flap for improved safety offering higher level of tightness
- Elasticated cuffs and ankles for good fit of garment openings
- Elasticated in waist for safe fit of garment and wearer comfort

Seams: External stitched seams for enhanced protection against penetration from outside to inside of garment

Colour:







White

Size: White S to XXXL
Carton Quantity: 100

Chemical Protective Garments, Category III



Type 5	Type 6	EN 1149-1	EN 1073-2
 *	 *	 **	 ***

Features

- Barrier against many inorganic chemicals in low concentrations and particles larger than 1µm
- Protection against particulate radioactive contamination
- Reliable Type 5 and 6 protection
- As a result of its unique manufacturing process, Tyvek® is permeable to air and water vapour
- Easy to dispose of, does not contain halogen compounds
- Garment design offers ease of movement to the wearer

Sizes

Body measurements in cm

Size	Chest girth (cm)	Body height (cm)
S	<92	<170
M	92 - 100	168 - 176
L	100 - 108	174 - 182
XL	108 - 116	180 - 188
XXL	118 - 124	186 - 194
XXXL	124 - 132	192 - 200



Tyvek.