



TM120S BU

DuPont™ ProShield® 6 SFR

DuPont™ ProShield® 6 SFR Coverall. Collar. Open Wrists and Ankles. Serged Seams. Blue.

Name	Description
Full Part Number	TM120SBUxx0025yy (xx=size;yy=option code)
Fabric/Materials	ProShield® 6 SFR
Design	Coverall w/ Open Wrists and Ankles
Seam	Serged
Color	Blue
Quantity/Box	25 per box
Option Codes	00,PI

FEATURES & PRODUCT DETAILS

ProShield® 6 SFR is a Lightweight, disposable overgarment designed to help protect and preserve primary flame-resistant garments. It provides a barrier against non-hazardous particles and aerosols while not contributing to burn injury.

ProShield® 6 SFR garments won't ignite and continue to burn when exposed to a flame source. They are flame retardant treated, not inherently flame resistant, and are intended to be worn over your primary flame resistant garments.


- Stormflaps.
- Laydown collar
- Open wrists
- Open ankles

AVAILABLE OPTIONS

Option Code	Description	Sizes	Part Number
00	Standard	SM,MD,LG,XL,2X,3X,4X,5X,6X	TM120SBUxx002500
PI	Standard_PI	MD,LG,XL,2X,3X,4X	TM120SBUxx0025PI

SPECIFICATIONS

- The garment shall have a collar.
- The garment shall have serged seams.
- The garment shall have open ankles.
- The garment shall be a coverall design.
- The garment shall have a front zipper closure.
- The garment shall be blue in color.
- The garment shall be constructed of DuPont™ ProShield® 6 SFR -- a nonwoven wood-pulp/polyester fabric that is treated to provide flame retardancy and liquid repellancy characteristics.
- The garment shall have an open wrist.



FINISHED DIMENSIONS

Size	Sleeve Length	Chest Width	Inseam	Fits Chest	Fits Height
SM	33 3/4	24 1/4	28	35 1/4 - 38 3/4	5'0" - 5'7"
MD	33 3/4	24 1/4	28	35 1/4 - 38 3/4	5'3" - 5'7"
LG	35	25 3/4	29	38 1/4 - 41 3/4	5'5" - 5'9"
XL	36 1/2	27 1/4	29 1/2	41 1/4 - 44 3/4	5'8" - 6'2"
2X	38 1/4	28 3/4	30 1/2	44 1/4 - 47 3/4	6'0" - 6'4"
3X	38 1/2	30 1/4	31 1/2	47 1/4 - 50 3/4	6'2" - 6'4"
4X	39 1/2	32	32 1/2	50 3/4 - 54 1/4	6'4" - 6'7"
5X	40	33 3/4	33 3/4	54 1/4 - 57 3/4	6'7" - 6'10"
6X	4 1/2	35 1/4	34 3/4	57 1/4 - 60 3/4	6'9" - 7'1"

ADDITIONAL EQUIPMENT NEEDED

- Temprow® garments are flame retardant treated, not inherently flame resistant, and are intended to be worn over primary flame-resistant garments. Temprow® garments will not provide thermal / fire protection if worn alone.
- Wear other appropriate PPE such as, but not limited to, respiratory, eye, head, hand, and foot protection based on the hazard assessment.

Physical Properties



Data relating to mechanical performance of the fabrics used in DuPont chemical protective clothing, listed for the selected garment according to the test methods and relevant European standard, if applicable. Such properties, including abrasion and flex-cracking resistance, tensile strength and puncture resistance can help in the assessment of protective performance.

Property	Test Method	Typical Result
Basis Weight	ASTM D3776	2.4 oz/yd ²
Breaking Strength - Grab (CD)	ASTM D5034	21 lb _f
Breaking Strength - Grab (MD).	ASTM D5034	27 lb _f
Surface Resistivity (25°C / 55% RH)	ASTM D257 (1081)	4.0 x 10 ⁷ ohms/square
Tear Resistance - Trap Tear (CD)	ASTM D1117	10 lb _f
Tear Resistance - Trap Tear (MD)	ASTM D1117	7 lb _f
Vertical Flame Resistance of Textiles	ASTM D6413	< 6 inches Char Damage
Vertical Flame Resistance of Textiles	ASTM D6413	< 2 seconds Afterflame

1 According to EN 14325 2 According to EN 14126 3 According to EN 1073-2 4 According to EN 14116 12
According to EN 11612 5 Front Tyvek ® / Back 6 Based on test according to ASTM D-572 7 See Instructions for
Use for further information, limitations and warnings > Larger than < Smaller than N/A Not Applicable STD DEV
Standard Deviation

WARNING

- *CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for informational use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact DuPont for specific data. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including, without limitation, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or its use.

Cellosolve® and Selexol™ are registered trademarks of Dow Chemicals Company. Skydrol® is a registered trademark of Solutia.

- *Liquid barrier performance varies based on the amount of liquid that may get on the garment, the length of time the liquid is on the garment, applied pressure and certain physical properties of the liquid. Tyvek®400, Tyvek® 400 D, ProShield®, ProShield® 10, ProShield® 60, Tyvek® 400 FC, and ProShield® 70 garments are not appropriate if during use they are getting wet (liquid is dripping or running, or it is wet to the touch) or if spotting is observed on skin or garments worn under the protective garment. Tyvek® 500 and Tyvek® 600 offer improved liquid barrier, but may not be appropriate if spotting is observed on the skin or garments worn under the protective garment. In applications where a higher liquid barrier is needed, consider Tychem® 2000 and Tychem® 4000 garments with taped seams.
- *Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.